

HLHGSA Hook Lift / Hydraulic Gantry / Hydraulic Sliding Arms, recommended for multiple height and length cans

- **Hydraulic Gantry 36" stroke, 1 3/4" bore, 1 1/4" piston rod (nitrited rod)**
- **3 1/2" x 3 1/2 3/16 gauge tube base section**
- **3" x 3" 3/16 gauge movable section**
- **4" x 2" x 3/16" top landing tube**
- **1/2" steel pivot mounts with 3/4" Teflon lined steel spherical bearings**
- **1/2" steel arch guide (Laser cut)**
- **(UHMW) self-lubricating guides**
- **Grade 8 bolts and nuts**
- **Pivot arm tubing (3" x 2" x 3/16") for the lower with steel welded ends**
- **(2 1/2" x 1 1/2" x 11 gauge) for the upper with steel welded ends**
- **Hydraulic Slide Arm cylinder 36" stroke 1 3/4" bore, 1 1/4" piston rod (nitrited rod)**
- **Powder Coated parts**
- **Hydraulics operate from trucks hydraulic system added valve sections**
- **Pivot cylinders have a 2 1/4" bore, 25" stroke with a 1 1/4" piston rod (nitrited rod)**
- **Gear driven flow divider for pivot cylinders and slide cylinders**
- **.25/3000 psi. hydraulic hose with #4 jic fittings**
- **3 1/2" steel torsion tube assembly with 1" steel 'tracking bar'**
- **Full 100% warranty on parts for two years (excluding cover)**