

**ROHGHS Roll Off / Hydraulic Gantry / Hydraulic Sliding Arms,
recommended for multiple height and length cans including 50 yd.**

- Hydraulic Gantry 36" stroke, 1 3/4" bore, 1 1/4" piston rod (nitrited rod)
- 3 1/2" x 3 1/2" x 3/16 gauge tube base section
- 3" x 3" x 3/16 gauge movable section
- 4" x 2" x 3/16" top landing tube
- 1/2" steel pivot mounts with 3/4" Teflon lined steel spherical bearings
- 1/2" steel arch guide (Laser cut)
- (UHMW) self-lubricating guides
- Grade 8 bolts and nuts
- Pivot arm tubing (3" x 2" x 3/16") for the lower with steel welded ends
- (2 1/2"x 1 1/2" x 11 gauge) for the upper with steel welded ends
- Hydraulic Slide Arm cylinder 36" stroke 1 3/4" bore, 1 1/4" rod (nitrited rod)
- Powder Coated Parts
- Hydraulics operate from trucks hydraulic system added valve sections
- Pivot cylinders have a 2 1/4" bore, 25" stroke with a 1 1/4" piston rod (nitrited rod)
- Gear driven flow divider for pivot cylinders and slide cylinders
- .25/3000 psi. hydraulic hose with #4 jic fittings
- 3 1/2" steel torsion tube assembly with 1" steel 'tracking bar'
- Full 100% warranty on parts for two years (excluding cover)